EV FERRULE & BOLTED TAG FUSE BLOCKS 10.3MM DIA.

adler


Part Number	Decsription
BH114-1C	Cartridge Fuse Block with 1/4" QC & Screw Terminals
BH114-1M	Flush Tag Fuse Block with Screw Terminals
BH114-CN	Cartridge / Tag Fuse Clear Cover - Non Indicating
BH114-CC	Cartridge Fuse Clear Cover With LED Indication
BH114-CL	Flush Tag Fuse Clear Cover With LED Indication




NEW

1100V

Cartridge Fuse Block Rating: 30A 1100VDC
Flush Tag Fuse Block Rating: 50A 1100VDC
Wire Size: 14-10 AWG (1.6 - 8.4mm2)
Material: Thermoplastic (Base & Cover).
Flammability: UL94VO (Base)
Operating Temperature: -40°C to +125°C
Terminals: Tin plated, copper alloy.
Mounting: Screw, bolt or 35mm DIN Rail.
Feature: Slide lock design.
Pack Size (box): 1, 10, 100
Notes: Fuse not included.
Approvals: TUV RoHS



Cartridge Fuse Block
Screw & 1/4" QC Terminals



Flush Tag Fuse Block
Screw Terminals

FUSE HOLDERS

RELATED PRODUCTS:




EVCartridge Fuse
(see p.32-34)



EV Flush Tag Fuse
(see p.32-34)



Gangable Slide Lock




Dimensions in MM

EV / EVSE BOLTED FUSE BLOCKS MODULAR

Bussmann

The C5268 series is a simple design modular fuse block. With this design, the fuse terminal and cable (with termination) are mounted on the same stud, minimizing labor needed for installation.


Part Number	Ampere Rating	Stud Diameter and Thread Type	"A" Stud Height
C5268-5	100A	1/4"-20 UNC (6.35mm)	1.75" (44.45mm)
C5268-3	200A	5/16"-18 UNC (7.93mm)	0.75" (19.05mm)
C5268-2	200A	5/16"-18 UNC (7.93mm)	1.75" (44.45mm)




Pack Size (box): 1 block (order 2 blocks per fuse).
Ambient Temp: 150 °C
Base: Plaslok S5440 phenolic, UL 94V-0 or 94V-1.
Studs: Steel, Zinc Plated
Hardware: Includes nut & spring washer.
Pack Size (box): 1, 50
Notes: Fuse not included.

Fuse blocks with fuse installed.







Dimensions in MM

RELATED PRODUCTS:



Class T Fuse
160V
(see p.31)



EV Fuse
500V - 800V
(see p.32-33)



EV Fuse
1000V
(see p.34)

PROLEC

Email: info@prolecproducts.com.au
Web: www.prolecproducts.com.au