Applications include battery chargers, 4x4's, caravans, RV's, trucks, buses, trolling motors, etc.

IGNITION PROTECTED

IP66*











12VDC Automatic TI Plastic Cover Parallel Bracket	12VDC - 24VDC Manual TIII Plastic Cover Parallel Bracket	12VDC Automatic TI Metal Cover Parallel Bracket	12VDC Automatic TI Metal Cover Cross Bracket	Ampere
Part Number	Part Number	Part Number	Part Number	Rating
121A05-B2P	123A05-B2P	121A05-B2M	121A05-A2M	5A
121A08-B2P	123A08-B2P	121A08-B2M	121A08-A2M	8A
121A10-B2P	123A10-B2P	121A10-B2M	121A10-A2M	10A
121A15-B2P	123A15-B2P	121A15-B2M	121A15-A2M	15A
121A20-B2P	123A20-B2P	121A20-B2M	121A20-A2M	20A
121A25-B2P	123A25-B2P	121A25-B2M	121A25-A2M	25A
121A30-B2P	123A30-B2P	121A30-B2M	121A30-A2M	30A
121A35-B2P	123A35-B2P	121A35-B2M	121A35-A2M	35A
121A40-B2P	123A40-B2P	121A40-B2M	121A40-A2M	40A
121A50-B2P	123A50-B2P	121A50-B2M	121A50-A2M	50A

Voltage: 14VDC (121 Series), 28VDC (123 & 124 series)
I.R.: 2.5kA @ 12VDC (Branch circuit protection). Contact sales for further info.
Operating Temperature: -40°C to 85°C. **Storage Temp.** -40°C to 125°C
Features: Ignition Protected
Ingress Protection Rating: IP66* (Plastic cover only, except terminals).
Mounting Hole: Bracket mounting holes 4.98 mm diameter.
Pack Size: Stock lines 1pc, indent items 250pcs.
Notes: Keps lock nuts included with circuit breakers.
Approvals: SAE J553, J1171


Terminal Specs:
2 x #10-32 studs



Plastic Cover Parallel Bracket




Metal Cover Parallel Bracket




Dimensions in MM

Metal Cover Cross Bracket



Connect the short stud to battery (+), connect the long stud to auxiliary circuit(s).



(2-3 position shown.)
Hole Slot 5.08 x 7.36mm

RELATED PRODUCTS:

Part Number	Description
CBBP	Clear Cover Parallel TIII ☐
CBBR	Red Terminal Boot PVC ■
CBBB2	Busbar 2 Position Brass Tin
CBBB3	Busbar 3 Position Brass Tin
CBBB4	Busbar 4 Position Brass Tin
CBBB5	Busbar 5 Position Brass Tin
CBBB6	Busbar 6 Position Brass Tin
CBBB8	Busbar 8 Position Brass Tin

Clear Cover



Terminal Boot



Push button to reset





Busbars





Notes: CBBP covers are IP64 water resistant. They protect the manual reset circuit breaker button against dust and water. The CBBR PVC boots protect terminal connections from accidental shorts. Use to comply with ABYC E-9, USCG 33pl & ISO 10133. Fits breakers with or without brackets. Both TI & TIII. Cable entry 18-10AWG. Busbars suitable for breakers fitted with a parallel bracket or without bracket.

PROLEC
Email: info@prolecproducts.com.au
Web: www.prolecproducts.com.au