Features:
- Ignition protected and weatherproof.
- Standard or 90 degree stud orientation.
- Robust thermoplastic case.
- Corrosion resistant studs & hardware.
- Largest amperage range available.
- 1/4" or 3/8" stainless steel stud options.
- Superior moisture seal.
- Breaker made in USA. Bracket made in AU.

MADE IN THE USA

IGNITION PROTECTED

IP67

MIL-STD

Auto Reset Type TI 1/4" Studs 3/8" Studs ^ Part Number	Manual Reset Type TIII PTT 1/4" Studs 3/8" Studs ^ Part Number	Ampere Rating	
171-P0-020	175-P0-020	20A	NEW
171-P0-025	175-P0-025	25A	
171-P0-030	175-P0-030	30A	
171-P0-035	175-P0-035	35A	
171-P0-040	175-P0-040	40A	
171-P0-050	175-P0-050	50A	
171-P0-060	175-P0-060	60A	
171-P0-070	175-P0-070	70A	
171-P0-080	175-P0-080	80A	
171-P0-090	175-P0-090	90A	
171-P0-100	175-P0-100	100A	
171-P0-110	175-P0-110	110A	
171-P0-120	175-P0-120	120A	
171-P0-135	175-P0-135	135A	
171-P0-150	175-P0-150	150A	
171-P0-175	175-P0-175	175A	
171-P0-200	175-P0-200	200A	
171-P2-225 ^	175-P2-225 ^	225A	NEW
171-P2-250 ^	174-P2-250 ^ *	250A	NEW
171-P2-275 ^	-	275A	NEW
171-P2-300 ^	-	300A	NEW

(^ 3/8" Stud only) * Not PTT - (Push To Trip) Manual reset only.

Auto Reset Type I Std. Orientation



Manual Reset Type III w/PTT Std. Orientation



Rear View 1/4" Studs Std. Orientation



Rear View 3/8" Studs Std. Orientation



I.R.Ratings:
Type TI (20A-150A): 3kA at 30VDC,
Type TI (175A-200A): 1.5kA at 30VDC.
Type TI (225A-300A): 2.5kA at 14VDC.
Type TIII (20A-150A): 2.5kA at 14VDC, 1.5kA at 48VDC .
Type TIII (175A-200A): 2.5kA at 14VDC, 1.5kA at 30VDC.
Type TIII (225A-250A): 1.5kA at 14VDC.

Voltage Ratings:
Type TI: (20A-200A): 30VDC, (225A-300A): 14VDC.
Type TIII: (20A-150A): 48VDC, (175A-200A): 30VDC.
Type TIII: (225A-250A): 14VDC.

Pack Size: Stock lines 1pc, indent items 9, 36, 72, 144pcs.
Housing: UL 94-V0 rated black thermoplastic.
Termination: 1/4" or 3/8" Stainless steel studs.
Terminal Hardware: Stainless steel Sems nuts included.
Operating Temp: -40°C to 85°C. **Ingress Protection Rating:** IP67
Indicator: Bright yellow colour reset mechanism provides visual indication of tripped condition on manual reset breakers (TIII).
Options: 90 Degree position studs suit horizontal busbar.
(17x-P1 Series is an indent item only)
Approvals: SAE J1625, J1171, ABYC E-11, MIL-STD-202, UL1077

Gasket Accessory
Part Number: B156-7003-J
Material: Black Santoprene.







NEW



Right Angle Mounting Bracket
Part Number: PROBRK017
Material: Stainless Steel



Dimensions in MM



PROLEC
Email: info@prolecproducts.com.au
Web: www.prolecproducts.com.au