
3AG FUSE HOLDERS PANEL MOUNT

Bussmann


Part Number	Knob Type	Terminal Type / Angle
HTB-26I-R	Fingergrip	1/4" Q/C (6.35mm) Straight
HTB-22I-R	Fingergrip	3/16" Q/C (4.8mm) Straight
HTB-34I-R	Screwdriver	3/16" Q/C (4.8mm) Right Angle

Voltage: 250V
Rating: 20A
Terminal Material: Tin plated brass.
Quick Connect Terminals: 1/4" or 3/16"
Solder Terminals: 3/16" can also be soldered.
Mounting Standard: Low profile, rear hex nut.
Mounting Option: High profile.
Ambient Temperature: -55°C to +85°C.
Body: Flame retardant thermoplastic UL 94VO.
Accessories: Includes plastic nut and spacer.
Options: Finger-grip type holders with 'splash proof' knob also available. Please contact sales.
Pack Size: 1, 10, 100
Note: Maximum panel Thickness: 7.62mm
Notes: Fuse is not included.
Approvals: RoHS




Finger Grip Knob





Screwdriver Knob





3/16" Terminal Type
Right 4.8mm (3/16")
Quick Connect (Q/C)
or Solder



3/16" Terminal Type
Straight 4.8mm (3/16")
Quick Connect (Q/C)
or Solder



1/4" Terminal Type
Straight 6.35mm (1/4")
Quick Connect (Q/C)

RELATED PRODUCTS:




AGC / 3AG Fuses
(see p.10 & 11)



3AB Fuses
(see p.11)

Mounting Hole Double D Type



Dimensions in MM

M205 300V IN-LINE HOLDER

Bussmann


NEW

Accepts both 5mm x 15mm or 5mm x 20mm cartidge fuses.

Part Number	Description
HHT	10A Bayonet holder



Voltage: 300VAC / 300VDC
Rating: 10A (M205), 5A (515)
Wire Thickness: 1mm² (#16 AWG)
Wire Length: 330mm Red loop
Wire Leads: Included **Terminals:** Brass
Temperature Rating: -40°C to +80°C
Pack Size: 1, 10, 100, 500, 1000
Approvals: RoHS



Dimensions in MM

RELATED PRODUCTS:



M205 Glass LBC Fuses
5 x 20mm



M205 Ceramic HBC Fuses
5 x 20mm



515 Glass LBC Fuses
5 x 20mm