EV BOLTED FUSE BLOCKS MODULAR 1000V

Bussmann


NEW
1000V
EV


Part Number	Description
BSCR101	Single Fuse Block M8 Stud





Rating: 500A
Voltage: 1000VAC / 1000VDC
Flammability Rating: UL 94-V0
Operating Temperature: -40°C to +125°C
Hardware: Includes hex nut & washer
Recommended Torque: 12 Nm.
Ordering Information: Sold as single blocks.
Approvals: RoHS







Dimensions in MM

FUSE COMPATIBILITY REFERENCE

Fuse Series	Amp Range
AE5..620	50A - 150A
AE5..625	100A - 250A
AE5..631	200A - 400A
AE5..638	400A - 500A
AE7..i25	60A - 150A
AE7..i38	175A - 400A
AEX..731	70A - 100A
AEX..738	125A - 200A
250GG	75A - 200A
ANL	35A - 500A
ANN	10A - 500A
EET	75A - 160A
EF3	100A - 500A
EFT	100A - 500A
FBT	35A - 500A
FEE	100A - 200A
FM	180A - 350A
FWA	500A - 500A
FWH	35A - 500A
FWJ	35A - 400A
FWP	35A - 400A
FWX	35A - 500A
JJN	110A - 400A
JJS	110A - 400A
LMT	160A - 450A
MT	160A - 355A
TPL/LI7T	300A - 500A

Not all recommended holders may be suitable for your circuit. Please check the holder specifications are suitable for your fuse.