HEAVY DUTY BATTERY FEEDER STUDS 3/8"

GEP POWER PRODUCTS

NEW

58V

MIL-STD

Features

- Military grade, power feed for applications through a firewall or bulkhead.
- Higher electrical rating and lower resistance due to a larger cross sectional area and the utilization of a higher conductive material.
- Increased installation torque values GEP's unique manufacturing.

Part Number	Stud	Hardware	Mtg Nut	Caps	Colour
PTR-38A-01	3/8"-16	Double Nuts SS	Stainless	Yes	Red
PTB-38A-01	3/8"-16	Double Nuts SS	Stainless	Yes	Black
PTR-38A-02	3/8"-16	Double Nuts SS	Nylon	Yes	Red
PTB-38A-02	3/8"-16	Double Nuts SS	Nylon	Yes	Black
PTR-38A-05	3/8"-16	Flange Nuts SS	Nylon	No	Red
PTB-38A-05	3/8"-16	Flange Nuts SS	Nylon	No	Black
C14-1003	N/A	IP67 Seal	Nylon	-	Black
SC10-2000A-B008	N/A	IP67 Seal Nut	Nylon	-	Red
SC10-2000A-B001	N/A	IP67 Seal Nut	Nylon	-	Black

PTB-38A-05





IP67 Seal Nut Black
SC10-2000A-B001




IP67 Seal Nut Red
SC10-2000A-B008



O-Ring Seal Black
C14-1003

Voltage: 58VDC **Rating:** 400A (2/0 or larger wire).
Grade: Commercial & Military.
Torque Rating: Body-Locknut-10 foot lbs.
Conductive Core: 110 Copper.
Studs: Stainless Steel (SS).
Body: Nylon 66,
Mounting Nut & Hardware: See above.
Options: Custom configuration, contact sales.

O-Ring Seal Ø 38.2



Panel Cutout Ø 33.4



Dimension in MM

PTB-38A-02
(with optional IP67 Seal nut)



PTR-38A-02
(assembled with included caps)



Overall Dimensions:
84 H x 57 W x 44 D (mm)

PTR-38A-02
(with optional IP67 Seal nut)



Overall Dimensions:
84H x 57 W x 49 D (mm)

PTB-38A-05



PTR-38A-05



Overall Dimensions:
64 H x 44 W x 44 D (mm)